



INSPECTION CERTIFICATE N° 2023/LHV/FE/IC03

BV Job Nr: LHV/19407109/04072023/IC3

PROJECT: Qualification of a valve as per ISO 15848-1:2015 + Amendment 1:2017

Ref: ERDET221102 01

BV Client: LATTY, FRANCE

P/o nr: POD-FR11-23-01980
(client to BV)

Manufacturer: LATTY, 28160 BROU, France

P/o nr: N.A.
(client to Manufacturer)

Inspection requested by: LATTY

SUPPLY / SUBJECT OF INSPECTION

Valve: HITER CONTROL VALVE 3"/#600 Drawing n°DDG-121358.001-22 dated 30/09/2022
 Size and Class: NPS3 Class 600
 Stem diameter: 19,05 mm
 Movement: Translation
 Packing set type: Packing composed with 2 x LATTYgraf 6995NG + 3 x LATTYflon 3265LM

Scope of inspection:

Place of inspection: LATTY, 28160 Brou, FRANCE
 Date of test: May 30 to June 22, 2023

➤ Reference documents used for inspection:

Standard specification: ISO 15848-1 dated on June 2015 + Amendment 1 dated on June 2017
 Test report: ERD14382/VCT rev.0 dated on July 3, 2023

➤ Results:

Fugitive emission tests have been performed with success in the sequence, as per above documents.

➤ Valve tests performances:

The test of the regulation valve "HITER CONTROL VALVE 3"/#600", Class 600, NPS 3, Stem diameter 19,05mm, meets the requirements of ISO 15848-1:2015 standard dated on June 2015 and Amendment 1 dated on June 2017 as follows:

ISO FE AH-CC3-SSA3- t200(RT;200°C) – CLASS 600 (102/88) - ISO15848-1(2015)+A1(2017)


According to ISO 15848-1:2015, stem diameter qualified rang is: 9,52mm to 38,10mm.

The undersigned, inspector to Bureau Veritas and acting within the scope of General Conditions of intervention of BUREAU VERITAS, has monitored "Fugitive Emission Test" in accordance with specifications.

Inspected by:

Name: S.GAIGEOT

Signature:



Checked by:

Name: /

Signature: /

Date of issue: July 4, 2023

Inspection centre: BV Harfleur

Distribution: ☒ CLIENT☐ MANUFACTURER